


RIDGELINE® CAP STYLE

SIGNATURE STYLE, PROVEN PROTECTION

Discover the ultimate in head protection with the Ridgeline® Cap Style hard hat. Its ABS shell delivers superior impact resistance and lightweight comfort, while the low-profile design ensures a modern, comfortable fit. Universal accessory slots make it easy to attach additional gear, and the adjustable 4-point or 6-point ratchet suspension fits sizes 6.5 to 8 securely.



FEATURES

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Effortless Adjustment: 4 or 6-point swinging ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Accessory Compatibility: Universal accessory slots to add additional protection

Low-Profile Design: Designed to ensure a modern and more comfortable fit

Enhanced Ventilation (For Select Models): Strategically placed vents improve airflow and reduce heat buildup, providing cooler wear during extended use


Hygienic Solution: Replaceable sweatband promotes cleanliness and comfort

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 Type I to ensure durability and confidence in performance



RIDGELINE® CAP STYLE

SIGNATURE STYLE, PROVEN PROTECTION



VARIATIONS

NON-VENTED

4-Point Ratchet Suspension | 21 Variations

- HP44110 White
- HP44111 Black
- HP44112 Gray
- HP44113 Slate Gray
- HP44116 Matte White Graphite Pattern
- HP44116S Shiny White Graphite Pattern
- HP44117 Matte Black Graphite Pattern
- HP44117S Shiny Black Graphite Pattern
- HP44118 Matte Copper Graphite Pattern
- HP44120 Red
- HP44121 Matte Red Graphite Pattern
- HP44122 Matte Blue Graphite Pattern
- HP44123 Matte Silver Graphite Pattern
- HP44124 Matte Lime Graphite Pattern
- HP44130 Yellow
- HP44131 Hi-Vis Lime
- HP44135 Green
- HP44141 Hi-Vis Orange
- HP44160 Blue
- HP44162 Light Blue
- HP44170 Pink

6-Point Ratchet Suspension | 7 Variations

- HP46110 White
- HP46120 Red
- HP46130 Yellow
- HP46131 Hi-Vis Lime
- HP46135 Green
- HP46141 Hi-Vis Orange
- HP46160 Blue

VENTED

4-Point Ratchet Suspension | 10 Variations

- HP44110V White
- HP44112V Gray
- HP44116SV Shiny White Graphite Pattern
- HP44117V Matte Black Graphite Pattern
- HP44120V Red
- HP44130V Yellow
- HP44131V Hi-Vis Lime
- HP44135V Green
- HP44141V Hi-Vis Orange
- HP44160V Blue



HP6PTSUS – Transforms 4-point suspensions to 6-point for cap style and full brim hard hats

REPLACEMENT PARTS



HPRBANDR – Ridgeline cap style and full brim hard hat sweat suspension



HPR461 – 6-point ratchet suspension



HPR441 – 4-point ratchet suspension

GENERAL SPECIFICATIONS

Weight: 358 gm
Shell Thickness: 2-4 mm
Dimensions: 28" x 22" x 15.2" cm
Suspension Adjust Sizing: 6.5 to 8
Suspension: Adjustable with Ratcheting Wheel

PRODUCT GUIDELINES

Never alter or modify the shell or suspension system. Always use original replacement parts. Decals/stickers are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.

Inspect your hard hat shell and suspension on a regular basis. Check for cracks or faulty parts each time it is to be used. If you notice any sign of damage, the faulty part should be discarded and immediately replaced. Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

The service life of a hard hat begins when the hard hat is put into service. Maximum service life is 5 years for the shell and 1 year for the suspension, beginning immediately upon first use. If the hard hat has received a considerable strike, it should be replaced immediately, even if there is no visible damage. Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water. DO NOT USE paints, chemicals, gasoline, or similar substances on the hard hat. If these substances are applied on the shell, its impact resistance and other features could be decreased and could be dangerous for the user.

Store hard hat in a cool place out of direct sunlight. Do not store in vehicles where the interior temperature can become extreme and cause deterioration of the hard hat.

MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic
Sweatband: Polyester + Polyurethane (PU) Foam
Suspension: HDPE (Polypropylene) + High Impact Nylon

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

MARKINGS

Standard: ANSI/ISEA Z89.1-2014
Type: Type I Cap Style Hard Hat
Class: Non-Vented – Class E (Electrical) Rated for 20,000 Volts, Vented – Class C (Conductive) Does Not Offer Electrical Protection – Class G (General) Rated for 2,200 Volts
LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F
HV: Meets All Requirements for High-Visibility (HP44131, HP44141, HP46131, HP46141, HP44131V, HP44141V)
Reverse Donning: ⚡ Indicates approval for assembling the suspension in the reverse direction for reverse wearing
Date Code: Indicates month and year shell was molded - does not indicate service life.

Product markings may vary // Updated as of 11.25